

ImmuniWeb's  
SSLScan API Documentation  
Version v2.0  
11<sup>th</sup> of April 2019

## Table of Contents

|  |    |
|--|----|
| Table of Contents.....                       | 2  |
| General Overview.....                        | 3  |
| Server Information.....                      | 5  |
| Certificates.....                            | 7  |
| NIST.....                                    | 16 |
| HIPAA.....                                   | 22 |
| PCI DSS.....                                 | 29 |
| Industry Best Practices.....                 | 35 |
| Email.....                                   | 39 |
| Third-party content.....                     | 42 |
| Results.....                                 | 43 |
| Highlights.....                              | 43 |
| Error handling.....                          | 44 |
| Appendix 1: Tag values list.....             | 45 |
| Appendix 2: List of Messages values.....     | 45 |
| Appendix 3: List of Descriptions values..... | 55 |
| Appendix 4: List of Highlights values.....   | 58 |
| Appendix 5: List of Titles values.....       | 62 |
| Appendix 6: List of Error messages.....      | 65 |

## General Overview

ImmuniWeb provides you with a free API to test your SSL/TLS servers. To assure high speed of service and availability for everyone, the free API allows 20 requests in 3 minutes, 250 requests in total per 24 hours, from one IP address.

In order to prevent abuse, a protection mechanism has been set up to remove the ability to test IPs that are not related to tested domain name. As a consequence, if a domain name is resolved into several IPs, a second request will be mandatory, specifying one of the IPs replied by the server along with the token issued (examples are below). However, if the tested domain name can be resolved into only one IP address, it will be immediately tested.

**License notice:** The API is provided for free both for private and commercial purposes. If you use the API for publicly available service (commercial or not) a link to ImmuniWeb's Free SSL Server Test is mandatory.

## API Specifications

| Field Name          | Value  |
|---------------------|--|
| <b>Protocol</b>     | HTTPS  |
| <b>Request Type</b> | POST   |
| <b>URL</b>          | https://www.immuniweb.com/ssl/api/v1/check/[ustamp].html - where "ustamp" is an arbitrary UNIX time-stamp (must be an integer). Such construction is done to prevent caching on client side. |

## POST Data Specification

| Field Name               | Value  |
|--------------------------|--|
| <b>domain:port</b>       | must be a valid domain name, or IP address, followed by a port number. If port is not supplied, 443 is used by default.                                  |
| <b>show_test_results</b> | "false" means that test results will be hidden, "true" means that test results will be displayed in statistics.  |
| <b>chosen_ip</b>         | IP address of tested server (if tested domain resolves to multiple addresses).   |
| <b>recheck</b>           | "false" will use results from cache if the server has been tested within the past 24 hours, "true" will perform a new test without looking at the cache. |
| <b>verbosity</b>         | 1 means output will be detailed, 0 means output will be short.   |
| <b>token</b>             | value of the token sent by the server if the tested domain is resolved into several IP addresses.  |

## Example of Transaction using CURL

```
# Step 1: Starting new test
$ curl -XPOST -d
'domain=twitter.com:443&chosen_ip=any&show_test_results=true&recheck=false&verbosity=1' 'https://www.immuniweb.com/ssl/api/v1/check/1451425590.html'

# Step 2.1: If test is not cached
{"debug":true,"job_id":"2a9e1f1bc92dc0c7a4bde930dff488771eea6d36988208d34163c5496227b8dc","status":"test_started","status_id":1,"message":"Test has started"}

# Step 2.2: If test is cached
{"test_id":"c84936eef26eeb8aaef5ffc43f38ddb91afd90ac27fb416bd0b21fe2edb1004","status":"test_cached","status_id":3,"message":"Test is cached"}

# Step 3: Fetch test results
$ curl -XPOST -d
'job_id=2a9e1f1bc92dc0c7a4bde930dff488771eea6d36988208d34163c5496227b8dc'
'https://www.immuniweb.com/ssl/api/v1/get_result/1451425590.html'

# Step 4: Test progress if test is not finished (if test is finished, see example response below)
{"job_id":"2a9e1f1bc92dc0c7a4bde930dff488771eea6d36988208d34163c5496227b8dc","status":"in_progress","status_id":2,"eta":2,"message":"Your test is in progress"}
```

The output array will be composed of the following main elements that will be detailed later in this document:

- **server\_info**: containing basic server info, like IP, port, reverse DNS...
- **certificates**: containing information about certs, graphs...
- **nist**: containing all information about NIST compliance
- **hipaa**: containing all information about HIPAA compliance
- **pci\_dss**: containing all information about PCI DSS compliance
- **industry\_best\_practices**: containing all information about industry best practices
- **third\_party\_content**: containing all the third party content
- **results**: containing the score and the grade
- **highlights**: containing the highlights

The most common syntax for elements is the following one:

```
{ "industry_best_practices":  
  "cert_ev": {  
    "value": true,  
    "message_id": 45,  
    "tag": 1,  
    "description_id": 0,  
    "title_id": 12,  
    "visible": true,  
    "message": "All the certificates provided by the server are  
Extended Validation (EV) certificates.",  
    "title": "CERTIFICATES PROVIDE EV"  
  }  
}
```

**value** contains the value for the configuration element, quite often it is a Boolean, but it can sometimes be a string, an integer or something else.

**message\_id** contains an integer, which is the id of the corresponding text message to display. Messages are defined in the appendix table of messages.

**tag** contains an integer, which is the id we currently use for colors and tags (information, good configuration...).

**description\_id**, just like message\_id contains an integer representing the id of the text that has to be shown when mouse is over the small "?" to provide more information. When it is set to 0 (empty), this means that no description is provided and then the small "?" infobox should not be displayed. Descriptions are defined in appendix table of descriptions.

**title\_id** contains an integer like for message\_id. This integer is the index of the title of the UI element that should be displayed.

**visible** contains a boolean acting like a flag to specify if the element must be displayed in UI or not. If set to true, the item must be displayed on UI, if false, it must not be.

**message** contains textual representation of corresponding message\_id

**title** contains textual representation of corresponding title\_id

## Server Information

Server information part contains different elements about server itself:

**"ip":**

- Syntax: { `value`: string, `tag`: int }
- Always present
- Description: the IP address tested

**“port”:**

- Syntax: { `value`: int, `tag`: int }
- Always present
- Description: the tcp port tested

**“hostname”:**

- Syntax: { `value`: string, `tag`: int }
- Always present
- Description: the hostname tested (can be an ip address)

**“reverse\_dns”:**

- Syntax: { `value`: string, `tag`: int }
- Always present
- Description: the reverse DNS for the IP tested

**“http\_response”:**

- Syntax: { `value`: string, `tag`: int }
- Absent if server does not support SSL/TLS
- Description: the HTTP response code to a GET request

**“server\_signature”:**

- Syntax: { `value`: string, `tag`: int }
- Absent if server does not support SSL/TLS
- Description: the content of Server HTTP Header

## Certificates

Certificates part include certificate information, chains and graphs the same way it was in the previous version, excepted that attributes names are now in lower\_case (snake case). It is composed of 3 main sub parts:

- **information**: a list containing detailed information about server certificates,
- **chain\_installation\_issues**: list of certificate chain insallation issues,
- **chains**: a list containing ordered certificates trust paths,
- **graphs**: a list containing the information needed to build graphs

### **Information:**

As mentioned, the information part is a list containing all server certificates. One server certificate has the following attributes:

#### **“key\_type”:**

- Syntax: string
- Always present
- Description: contains the type of key associated (RSA, ECDSA...)

#### **“key\_size”:**

- Syntax: int
- Always present
- Description: contains the size of the key associated in bits

#### **“signature\_algorithm”:**

- Syntax: string
- Always present
- Description: contains the signature algorithm used to sign the certificate

#### **“cn”:**

- Syntax: string

- Always present
- Description: contains Common Name of the certificate

**“san”:**

- Syntax: string
- Always present
- Description: contains the Subject AltNames for which the certificate is valid

**“transparency”:**

- Syntax: bool
- Always present
- Description: set to true if the certificate provides transparency

**“ev”:**

- Syntax: bool
- Always present
- Description: set to true if the certificate provides Extended Validation

**“valid\_from”:**

- Syntax: int (timestamp)
- Always present
- Description: the date from which the certificate is valid

**“valid\_to”:**

- Syntax: int (timestamp)
- Always present
- Description: the expiration date of the certificate

**“valid\_now”:**

- Syntax: bool
- Always present
- Description: set to true if the certificate is valid at the time of testing



**“expires\_soon”:**

- Syntax: bool
- Always present
- Description: set to true if the certificate expires in less than 30 days

**“self\_signed”:**

- Syntax: bool
- Always present
- Description: set to true if the certificate is self-signed

**“ocsp\_must\_staple”:**

- Syntax: bool
- Always present
- Description: set to true if the certificate has must staple extension

**“supports\_ocsp\_stapling”:**

- Syntax: bool
- Always present
- Description: set to true if the certificate supports OCSP stapling

**“valid\_for\_host”:**

- Syntax: bool
- Always present
- Description: set to true if the certificate is valid for the domain tested

**“revoked”:**

- Syntax: bool
- Always present
- Description: set to true if the certificate has been revoked

**“known\_issuer”:**

- Syntax: bool

- Always present
- Description: set to true if the CA that signed the certificate is trusted

**“trusted”:**

- Syntax: bool
- Always present
- Description: set to true if the certificate can be trusted

**Chain installation issues:**

This section is a list of several installation issue checkups for server certificates. There's a boolean field '**value**' which is set to '**True**' if there is any issue detected, along with it is an array '**results**' annotating the results of separate checks. The structure is as follows:

**“chain\_installation\_issues”:**

- Syntax: { **value**: bool, **results**: array }
- Description: value set to True if there is any issue detected, results array populated with separate issue check results.

The structure of the '**results**' array is as follows:

**“is\_chain\_complete”:**

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int }
- Description: set to true if server sends intermediate certs for at least one chain

**“has\_sent\_root\_ca”:**

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int }
- Description: set to true if the server sends root CA in the cert chain

**“is\_order\_correct”:**

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int }
- Description: set to true if certificate chain was provided in correct order

**“has\_sent\_extra\_certs”:**

- Syntax: { `value`: bool, `message_id`: int, `tag`: int }
- Description: set to true if server has sent certs that were not expected

**Chains:**

The chain part is a list of certificate chains that have been reconstructed from the server certificates. A certificate chain is an ordered list of certificates from the server certificate (leaf certificate) to the root CA certificate.

Information provided about the certificates are different as we need at the same time less detailed information and some specific information for instance about HPKP. The attributes of a certificate are the following:

**“sha256”:**

- Syntax: string
- Always present
- Description: contains the sha256 sum of the certificate

**“cn”:**

- Syntax: string
- Always present
- Description: contains Common Name of the certificate

**“key\_type”:**

- Syntax: string
- Always present
- Description: contains the type of key associated (RSA, ECDSA...)

**“key\_size”:**

- Syntax: int
- Always present
- Description: contains the size of the key associated in bits

**“signature\_algorithm”:**

- Syntax: string
- Always present
- Description: contains the signature algorithm used to sign the certificate

**“valid\_to”:**

- Syntax: int (timestamp)
- Always present
- Description: the expiration date of the certificate

**“pin”:**

- Syntax: string
- Always present
- Description: the pin of the corresponding public key, used in HPKP

**“matches\_hpkp”:**

- Syntax: bool
- Always present
- Description: set to true if this certificate is pinned

**“cert\_type”:**

- Syntax: string
- Always present
- Description: contains the type of the cert among:
  - Server certificate
  - Intermediate CA
  - Root CA

**“comment”:**

- Syntax: string
- Always present, can be empty
- Description: contains a comment about the certificate among:

- Self-signed
- Extended Validation

**“weak\_key\_size”:**

- Syntax: bool
- Always present
- Description: set to true if key size is small for specific signature algorithm

**“weak\_signature\_algorithm”:**

- Syntax: bool
- Always present
- Description: set to true if signature algorithm is weak

**Graphs:**

The graphs part contains mainly the same information as the chains part, but with level and children information and trying to remove duplicates from chains. This way, it is possible to draw relationships between certificates.

This section is a list of certificate graphs, each graph being a list of certificates having the following attributes:

**“sha256”:**

- Syntax: string
- Always present
- Description: contains the sha256 sum of the certificate

**“cn”:**

- Syntax: string
- Always present
- Description: contains Common Name of the certificate

**“key\_type”:**

- Syntax: string
- Always present
- Description: contains the type of key associated (RSA, ECDSA...)

**“key\_size”:**

- Syntax: int
- Always present
- Description: contains the size of the key associated in bits

**“signature”:**

- Syntax: string
- Always present
- Description: contains the signature algorithm used to sign the certificate

**“valid\_to”:**

- Syntax: int (timestamp)
- Always present
- Description: the expiration date of the certificate

**“pin”:**

- Syntax: string
- Always present
- Description: the pin of the corresponding public key, used in HPKP

**“matches\_hpkp”:**

- Syntax: bool
- Always present
- Description: set to true if this certificate is pinned

**“cert\_type”:**

- Syntax: string

- Always present
- Description: contains the type of the cert among:
  - Server certificate
  - Intermediate CA
  - Root CA

**“comment”:**

- Syntax: string
- Always present, can be empty
- Description: contains a comment about the certificate among:
  - Self-signed
  - Extended Validation

**“children\_hashes”:**

- Syntax: list of strings
- Always present, can be empty
- Description: every string contained in this list is the sha256 sum of certificates that have been signed with the current one

**“tree\_levels”:**

- Syntax: list of integers
- Always present
- Description: every integer contained in this list corresponds to the level of the certificate in the chain, starting from the server certificate. Server certificates have level=0.

## NIST

NIST part contains all information related to NIST compliance:

### **“cert\_x509\_v3”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS
- Description: set to true if server certificate is an X509 certificate in version 3

### **“cert\_self\_signed”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS
- Description: set to true if server cert is self-signed

### **“cert\_provides\_revocation\_information”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS
- Description: set to true if certificate provides revocation information

### **“cert\_small\_key”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS
- Description: set to true if the private key is too small

### **“cert\_signature\_algorithm\_mismatch”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS
- Description: set to true if the cert has been signed with a wrong algorithm



**“cert\_weak\_signature”:**

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS
- Description: set to true if the cert has not been signed using SHA2

**“supported\_protocols”:**

- Syntax: the element is a list of arrays having the following syntax: { **value**: string, **tag**: int }. Only supported versions are present:

```
{ "nist":  
  { "supported_protocols": [  
    { "value": "SSLv3", "tag": 2 },  
    { "value": "TLSv1.1", "tag": 1 }  
  ] },  
}
```

- Absent if server does not support SSL/TLS
- Description: lists supported protocols

**“supports\_invalid\_protocols”:**

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS
- Description: set to true if server supports protocols that are not approved by NIST

**“supported\_cipher\_suites”:**

- Syntax: the element is a list of arrays having the following syntax: { **value**: string, **tag**: int, **protocols**: array }. Only supported cipher suites are present:

```
{ "nist": { "supported_cipher_suites": [
```

```
{ "value": "TLS_RSA_WITH_CAMELLIA_128_CBC_SHA",  
  "tag": 2,  
  "protocols": ["TLSv1.0", "TLSv1.1"]  
},  
{ "value": "TLS_DHE_RSA_WITH_AES_256_GCM_SHA384",  
  "tag": 1,  
  "protocols": ["TLSv1.2"]  
}  
] } }
```

- Absent if server does not support SSL/TLS
- Description: lists supported cipher suites

#### **"supports\_invalid\_cipher\_suites":**

- Syntax: { value: bool, message\_id: int, tag: int, description\_id: int, title\_id: int, visible: bool }
- Absent if server does not support SSL/TLS
- Description: set to true if server supports cipher suites that are not approved by NIST

#### **"dh\_parameter\_size":**

- Syntax: { value: int, message\_id: int, tag: int, description\_id: int, title\_id: int, visible: bool }
- Absent if server does not support SSL/TLS or if server does not support DH suites
- Description: gives the size of the Diffie-Hellman parameter in bits

#### **"dh\_parameter\_weak":**

- Syntax: { value: bool, message\_id: int, tag: int, description\_id: int, title\_id: int, visible: bool }
- Absent if server does not support SSL/TLS or if server does not support DH suites

- Description: set to true if the Diffie-Hellman parameter size is below NIST requirements (2048)

**“supported\_elliptic\_curves”:**

- Syntax: the element is a list of arrays having the following syntax: { **value**: string, **size**: int, **tag**: int }. Only supported curves are present:

```
{ "nist": {"supported_protocols": [  
    { "value": "P-521 (secp521r1)", "size": 521, "tag": 1 },  
    { "value": "P-384 (secp384r1)", "size": 384, "tag": 1 },  
  ] }  
}
```

- Absent if server does not support SSL/TLS or if server does not support elliptic curves
- Description: lists supported elliptic curves

**“supports\_invalid\_curves”:**

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS or if server does not support elliptic curves
- Description: set to true if server supports elliptic curves that are not approved by NIST

**“supports\_mandatory\_curves”:**

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS or if server does not support elliptic curves

**“supports\_tlsv1.1”:**

- Description: set to true if server supports at least one of the mandatory curves

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS
- Description: set to true if server supports TLSv1.1

**“missing\_mandatory\_ciphers”:**

- Syntax: the element is a list of arrays having the following syntax: { **value**: string, **tag**: int }. Only missing ciphers that are mandatory are present:

```
{ "nist": {"missing_mandatory_ciphers": [  
    { "value": "TLS_RSA_WITH_AES_128_CBC_SHA",  
      "tag": 2,  
      "protocols": ["TLSv1.0", "TLSv1.1", "TLSv1.2"],  
    },  
    { "value": "TLS_RSA_WITH_3DES_EDE_CBC_SHA",  
      "tag": 2,  
      "protocols": ["TLSv1.0", "TLSv1.1"],  
    }  
  ] }  
}
```

- Absent if server does not support SSL/TLS, empty if no mandatory cipher is missing
- Description: lists missing ciphers

**“has\_all\_mandatory\_ciphers”:**

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS
- Description: set to false if server is missing mandatory ciphers

**“supports\_ocsp\_stapling”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS or if no certificate has OCSP URI set
- Description: set to true if server supports OCSP stapling

**“provides\_reneg\_information”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS
- Description: set to true if server say if it supports or not secure renegotiation

**“ec\_point\_format”:**

- Syntax: { **value:** mixed, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS or if server does not support elliptic curves
- Description: set to true if server supports ec point format TLS extension, false if not and “not\_present” if server doesn’t send TLS Extension.

**“compliant”:**

- Syntax: { **value:** bool }
- Absent if server does not support SSL/TLS
- Description: set to true if server is compliant with NIST guidelines

## HIPAA

HIPAA part contains all information related to HIPAA compliance:

### “cert\_x509\_v3”:

- Syntax: { value: bool, message\_id: int, tag: int, description\_id: int, title\_id: int, visible: bool }
- Absent if server does not support SSL/TLS
- Description: set to true if server certificate is an X509 certificate in version 3

### “cert\_self\_signed”:

- Syntax: { value: bool, message\_id: int, tag: int, description\_id: int, title\_id: int, visible: bool }
- Absent if server does not support SSL/TLS
- Description: set to true if server cert is self-signed

### “cert\_provides\_revocation\_information”:

- Syntax: { value: bool, message\_id: int, tag: int, description\_id: int, title\_id: int, visible: bool }
- Absent if server does not support SSL/TLS
- Description: set to true if certificate provides revocation information

### “cert\_small\_key”:

- Syntax: { value: bool, message\_id: int, tag: int, description\_id: int, title\_id: int, visible: bool }
- Absent if server does not support SSL/TLS
- Description: set to true if the private key is too small

### “cert\_signature\_algorithm\_mismatch”:

- Syntax: { value: bool, message\_id: int, tag: int, description\_id: int, title\_id: int, visible: bool }
- Absent if server does not support SSL/TLS
- Description: set to true if the cert has been signed with a wrong algorithm

### “cert\_weak\_signature”:

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS
- Description: set to true if the cert has not been signed using SHA2

### “supported\_protocols”:

- Syntax: the element is a list of arrays having the following syntax: { **value**: string, **tag**: int }. Only supported versions are present:

```
{ "nist": {"supported_protocols": [  
    { "value": "SSLv3", "tag": 2 },  
    { "value": "TLSv1.1", "tag": 1 }  
  ] }  
}
```

- Absent if server does not support SSL/TLS
- Description: lists supported protocols

### “supports\_invalid\_protocols”:

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS
- Description: set to true if server supports protocols that are not approved by HIPAA

### “supported\_cipher\_suites”:

- Syntax: the element is a list of arrays having the following syntax: { **value**: string, **tag**: int, **protocols**: array }. Only supported cipher suites are present:

```
{ "hipaa": {"supported_cipher_suites": [  
    { "value": "TLS_RSA_WITH_AES_128_CBC_SHA",
```

```
    "tag": 2,  
    "protocols": ["TLSv1.1", "TLSv1.2"]  
  },  
  { "value": "TLS_RSA_WITH_3DES_EDE_CBC_SHA",  
    "tag": 1,  
    "protocols": ["TLSv1.1"]  
  }  
] }  
}
```

- Absent if server does not support SSL/TLS
- Description: lists supported cipher suites

#### “supports\_invalid\_cipher\_suites”:

- Syntax: { value: bool, message\_id: int, tag: int, description\_id: int, title\_id: int, visible: bool }
- Absent if server does not support SSL/TLS
- Description: set to true if server supports cipher suites that are not approved by HIPAA

#### “dh\_parameter\_size”:

- Syntax: { value: int, message\_id: int, tag: int, description\_id: int, title\_id: int, visible: bool }
- Absent if server does not support SSL/TLS or if server does not support DH suites
- Description: gives the size of the Diffie-Hellman parameter in bits

#### “dh\_parameter\_weak”:

- Syntax: { value: bool, message\_id: int, tag: int, description\_id: int, title\_id: int, visible: bool }



- Absent if server does not support SSL/TLS or if server does not support DH suites
- Description: set to true if the Diffie-Hellman parameter size is below HIPAA requirements (2048)

**“supported\_elliptic\_curves”:**

- Syntax: the element is a list of arrays having the following syntax: { **value**: string, **size**: int, **tag**: int }. Only supported curves are present:

```
{ "hipaa":  
  {"supported_elliptic_curves": [  
    {  
      "value": "P-521 (secp521r1)",  
      "size": 521,  
      "tag": 1  
    },  
  
    {  
      "value": "P-384 (secp384r1)",  
      "size": 384,  
      "tag": 1  
    }  
  ] }  
}
```

- Absent if server does not support SSL/TLS or if server does not support elliptic curves
- Description: lists supported elliptic curves

**“supports\_invalid\_curves”:**

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS or if server does not support elliptic curves
- Description: set to true if server supports elliptic curves that are not approved by HIPAA

**“supports\_mandatory\_curves”:**

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS or if server does not support elliptic curves
- Description: set to true if server supports at least one of the mandatory curves

**“supports\_tlsv1.1”:**

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS
- Description: set to true if server supports TLSv1.1

**“missing\_mandatory\_ciphers”:**

- Syntax: the element is a list of arrays having the following syntax: { **value**: string, **tag**: int }. Only missing ciphers that are mandatory are present:

```
{ "nist":  
  { "missing_mandatory_ciphers": [  
    { "value": "TLS_RSA_WITH_AES_128_CBC_SHA", "tag": 2 },  
    { "value": "TLS_RSA_WITH_3DES_EDE_CBC_SHA", "tag": 2 }  
  ] }  
}
```

- Absent if server does not support SSL/TLS, empty if no mandatory cipher is missing
- Description: lists missing ciphers

**“has\_all\_mandatory\_ciphers”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS
- Description: set to false if server is missing mandatory ciphers

**“supports\_ocsp\_stapling”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS or if no certificate has OCSP URI set
- Description: set to true if server supports OCSP stapling

**“provides\_reneg\_information”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS
- Description: set to true if server say if it supports or not secure renegotiation

**“ec\_point\_format”:**

- Syntax: { **value:** mixed, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS or if server does not support elliptic curves
- Description: set to true if server supports ec point format TLS extension, false if not and “not\_present” if server doesn’t send TLS Extension.

**“compliant”:**

- Syntax: { **value:** bool }
- Absent if server does not support SSL/TLS
- Description: set to true if server is compliant with HIPAA



PUBLIC

## PCI DSS

### “cert\_small\_key”:

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS
- Description: set to true if the private key is too small

### “cert\_weak\_signature”:

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS
- Description: set to true if the cert has not been signed using SHA2

### “cert\_trusted”:

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS
- Description: set to true if the cert could be trusted

### “supported\_protocols”:

- Syntax: the element is a list of arrays having the following syntax: { **value**: string, **tag**: int }. Only supported versions are present:

```
{ "pci_dss":  
  { "supported_protocols": [  
    { "value": "SSLv3", "tag": 2 },  
    { "value": "TLSv1.1", "tag": 1 }  
  ] }  
}
```

- Absent if server does not support SSL/TLS
- Description: lists supported protocols

**“supports\_invalid\_protocols”:**

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS
- Description: set to true if server supports protocols that are not approved by PCI DSS

**“supported\_cipher\_suites”:**

- Syntax: the element is a list of arrays having the following syntax: { **value**: string, **tag**: int, **protocols**: array }. Only supported cipher suites are present:

```
{ "pci_dss":  
  {"supported_cipher_suites": [  
    { "value": "TLS_RSA_WITH_AES_128_CBC_SHA",  
      "tag": 2,  
      "protocols": ["TLSv1.1", "TLSv1.2"]  
    },  
    { "value": "TLS_RSA_WITH_3DES_EDE_CBC_SHA",  
      "tag": 1,  
      "protocols": ["TLSv1.1"]  
    }  
  ] }  
}
```

- Absent if server does not support SSL/TLS
- Description: lists supported cipher suites

**“supports\_invalid\_cipher\_suites”:**

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS
- Description: set to true if server supports cipher suites that are not approved by PCI DSS

**“dh\_parameter\_size”:**

- Syntax: { **value**: int, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS or if server does not support DH suites
- Description: gives the size of the Diffie-Hellman parameter in bits

**“dh\_parameter\_weak”:**

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS or if server does not support DH suites
- Description: set to true if the Diffie-Hellman parameter size is below PCI DSS requirements (2048)

**“supported\_elliptic\_curves”:**

- Syntax: the element is a list of arrays having the following syntax: { **value**: string, **size**: int, **tag**: int }. Only supported curves are present:

```
{ "pci_dss":  
  { "supported_elliptic_curves": [  
    {  
      "value": "P-521 (secp521r1)",  
      "size": 521,  
      "tag": 1  
    },  
  ],  
}
```

```
{  
    "value": "P-384 (secp384r1)",  
    "size": 384,  
    "tag": 1  
}  
  
] }  
  
}
```

- Absent if server does not support SSL/TLS or if server does not support elliptic curves
- Description: lists supported elliptic curves

#### **“supports\_invalid\_curves”:**

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS or if server does not support elliptic curves
- Description: set to true if server supports elliptic curves that are not approved by PCI DSS

#### **“poodle\_tls”:**

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS
- Description: result of the poodle over TLS test

#### **“cve\_2016\_2107”:**

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS



- Description: result of the CVE-2016-2107 test

**“supports\_insecure\_reneg”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS
- Description: set to true if the server supports client-initiated insecure renegotiation

**“heartbleed”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS
- Description: set to true if the server is vulnerable to heartbleed

**“cve\_2014\_0224”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS or if test requires STARTTLS
- Description: result of the poodle over TLS test

**“drown”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS
- Description: set to true if the server is vulnerable to drown

**“poodle\_ssl”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS

- Description: set to true if the server is vulnerable to poodle over SSL

**“robot”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if the server does not support SSL/TLS or does not allow connections with TLS\_RSA
- Description: set to true if the server is vulnerable to ROBOT

**“compliant”:**

- Syntax: { **value:** bool }
- Absent if server does not support SSL/TLS
- Description: set to true if server is compliant with PCI DSS requirements

## Industry Best Practices

This part is about best practices.

### “cert\_valid\_too\_long”:

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS
- Description: set to true if cert has been signed for more than 3 years

### “cert\_ev”:

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS
- Description: set to true if cert provides with Extended Validation

### “http\_to\_https\_redirect”:

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS or if an error occurs with this test
- Description: set to true if server redirects from HTTP to HTTPS

### “https\_to\_http\_redirect”:

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if there is no redirection from HTTPS to HTTP
- Description: set to true if server redirects from HTTPS to HTTP

### “mixed\_content”:

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS or if an error occurs with this test
- Description: set to true if HTTP content is included into HTTPS

**“supports\_tlsv1.3”:**

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS
- Description: set to true if the server supports TLSv1.3

**“has\_preference”:**

- Syntax: { **value**: bool, **message\_id**: int, **tag**: int, **description\_id**: int, **title\_id**: int, **visible**: bool }
- Absent if server does not support SSL/TLS
- Description: set to true if server cipher suite preference is enabled

**“cipher\_preference”:**

- Syntax: the element is a list of arrays having the following syntax: { **protocol**: string, **value**: string, **size**: int, **tag**: int } :

```
{ "industry_best_practices":  
  { "cipher_preference": [  
    {  
      "protocol": "TLSv1.0",  
      "value": "TLS_DHE_RSA_WITH_AES_256_CBC_SHA",  
      "tag": 1  
    },  
    {  
      "protocol": "TLSv1.2",  
      "value": "TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384",  
      "tag": 1  
    }  
  ] }  
}
```

- Absent if server does not support SSL/TLS, empty if server has no preference
- Description: lists cipher suites preferred per protocol

**“prefers\_weak\_ciphers”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS
- Description: set to true if the server prefers cipher suites that have not been approved by PCI DSS

**“prefers\_pfs”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS
- Description: set to true if server prefers cipher suites providing Perfect Forward Secrecy

**“supports\_fallback\_scsv”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS or if TLS Fallback SCSV is not needed (server supports only 1 protocol)
- Description: set to true if server supports TLS Fallback SCSV

**“supports\_client\_initiated\_reneg”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS
- Description: set to true if server supports client-initiated renegotiation

**“supports\_secure\_reneg”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }

- Absent if server does not support SSL/TLS or if server does not provide information regarding support
- Description: set to true if server supports secure renegotiation

#### **“tls\_compression”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS
- Description: set to true if server supports TLS compression

#### **“has\_hsts”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS or is not a web server
- Description: set to true if server enforces HSTS

#### **“hsts\_duration”:**

- Syntax: { **value:** int, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS or does not support HSTS
- Description: this is the duration of HSTS max-age in seconds

#### **“hsts\_long”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS or does not support HSTS
- Description: set to true if server’s HSTS max-age is above 180 days

#### **“has\_hpkp”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS or is not a web server
- Description: set to true if server has HPKP header

#### **“hpkp\_valid”:**

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS or does not support HPKP
- Description: set to false if HPKP syntax is invalid or if no pin match

#### “hpkp\_duration”:

- Syntax: { **value:** int, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS or HPKP is invalid
- Description: this is the duration of HPKP max-age in seconds

#### “hpkp\_long”:

- Syntax: { **value:** bool, string, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Absent if server does not support SSL/TLS or HPKP is invalid
- Description: set to true if server’s HPKP max-age is above 60 days

#### “early\_data”:

- Syntax: { **value:** bool, **message\_id:** int, **tag:** int, **description\_id:** int, **title\_id:** int, **visible:** bool }
- Description: set to true if server supports 0-RTT early data

## Email

This section lists SPF, DMARC and DKIM server security hardenings. This section is present only if tested host is email service.

**SPF** - is simple email-validation system designed to detect email spoofing by providing a mechanism to allow receiving mail exchangers to check that incoming email from a domain comes from a host authorized by that domain's administrators.

```
{
  'values': [
    {
      'raw': string
      'messages': [],
    }
  ],
  'highlights': [
    {
      'highlight': string,
      'highllight_id': int,
      'tag': int
    }
  ],
  'title': string,
  'title_id': integer,
  'description': string,
  'description_id': int,
  visible: boolean,
}
```

**DMARC** - is an email-validation system designed to detect and prevent email spoofing.

```
{
```



```
'values': [  
  {  
    'raw': string  
    'messages': [],  
  }  
],  
'highlights': [  
  {  
    'highlight': string,  
    'highlight_id': int,  
    'tag': int  
  }  
],  
'title': string,  
'title_id': integer,  
'description': string,  
'description_id': int,  
visible: boolean,  
}
```

**DKIM** - DomainKeys Identified Mail (DKIM) provides email authentication and helps prevent potentially malicious emails from reaching recipients by using a digital signature in the email header. This validates that the email originated from the correct location and was not tampered with in transit. This also protects the reputation of the supposed sender of the email.

```
{  
  'values': [  
    {  
      'raw': string  
      'messages': [],  
    }  
  ],  
  'highlights': [  
    {  
      'highlight': string,  
      'highlight_id': int,  
      'tag': int  
    }  
  ],  
  'title': string,  
  'title_id': integer,  
  'description': string,  
  'description_id': int,  
  visible: boolean,  
}
```

```
{
  'raw': string
  'messages': [],
}
],
'highlights': [
  {
    'highlight': string,
    'highllight_id': int,
    'tag': int
  }
],
'title': string,
'title_id': integer,
'description': string,
'description_id': int,
visible: boolean,
}
```

## Third-party content

This part lists all third-party content found on index page. Tag values are 1 when content is fetched using HTTPS or 3 otherwise.

```
{ "third_party_content": [
  { "value": string, "tag": int },
  ...
]
```

```
] }
```

## Results

Results part contains the main results. The attributes are the following:

### **“has\_ssl\_tls”:**

- Syntax: boolean
- Always present
- Description: set to true if server supports SSL/TLS

### **“score”:**

- Syntax: int
- Always present
- Description: server’s score

### **“grade”:**

- Syntax: string
- Always present
- Description: server’s grade

## Highlights

This part lists highlights in an ordered way. The syntax is the following:

```
{ "highlights": [  
  { "highlight_id": int, "tag": int, "highlight": string },  
  ...  
] }
```

Just like “message\_id” or “description\_id”, “highlight\_id” contains the index where to find the appropriate text in appendix table of messages, descriptions and highlights.

## Error handling

If an error occurs, only basic information and an error message will be returned the following way:

```
{ "error": string }
```

or

```
{ "error": string, "server_info": {  
    "ip": string,  
    "port": int,  
    "hostname": string,  
    "reverse_dns": string  
} }
```

Possible error messages which system can return are:

- You have performed N tests in the last 3 minutes. The system is currently busy, please try again later.
- Domain name was resolved to an invalid IP address.
- Invalid IP address.
- The domain name does not exist.
- An error occurred while testing server configuration, server became unreachable during the test.

## Appendix 1: Tag values list

Below is a reminder of the list of tags that are used:

| Tag value | Description                                |
|-----------|--|
| 0         | Nothing, empty                             |
| 1         | Good configuration                         |
| 2         | Non-compliant with NIST guidelines         |
| 3         | Misconfiguration or weakness               |
| 4         | Information                                |
| 5         | Non-compliant with PCI DSS requirements    |
| 6         | Not compliant with NIST and PCI DSS        |
| 7         | Not vulnerable                             |
| 8         | Deprecated. Dropped in Jun 2018            |
| 9         | Non-compliant with HIPAA guidance          |
| 10        | Non-compliant with NIST and HIPAA          |
| 11        | Non-compliant with HIPAA and PCI DSS       |
| 12        | Non-compliant with NIST, HIPAA and PCI DSS |

## Appendix 2: List of Messages values

| ID | Value   |
|----|---|
| 1  | The version of the RSA X509 certificate provided by the server is prior to version 3 (the latest one).                    |
| 2  | The version of the ECDSA X509 certificate provided by the server is prior to version 3 (the latest one).                  |
| 3  | The version of the following X509 certificates provided by the server is prior to version 3 (the latest one): RSA, ECDSA. |
| 4  | Some of the X509 certificates provided by the server are prior to version 3 (the latest one).                             |
| 5  | All the X509 certificates provided by the server are in version 3.  |
| 6  | The RSA certificate provided by the server is self-signed.  |

- 7 The ECDSA certificate provided by the server is self-signed.
- 8 The following certificates are self-signed: RSA, ECDSA.
- 9 Some of the certificates provided by the server are self-signed.
- 10 All the certificates provided by the server have been signed by a CA.
- 11 The RSA certificate provided is missing OCSP URI and crlDistributionPoints extension, making impossible to verify if it has been revoked.
- 12 The ECDSA certificate provided is missing OCSP URI and crlDistributionPoints extension, making impossible to verify if it has been revoked.
- 13 The following certificates are missing OCSP URI and crlDistributionPoints extension, making impossible to verify if they have been revoked: RSA, ECDSA.  
Some of the certificates provided are missing OCSP URI and
- 14 crlDistributionPoints extension, making impossible to verify if they have been revoked.
- 15 All the certificates sent by the server provide ways to check their revocation status.
- 16 The RSA certificate's key length is too small.
- 17 The ECDSA certificate's key length is too small.
- 18 The following certificates' key lengths are too small: RSA, ECDSA.
- 19 Some of the certificates have a public key that is too small.
- 20 All the certificates provided have public keys that are long enough.
- 21 The RSA certificate provided has not been signed using the proper algorithm according to NIST guidelines.
- 22 The ECDSA certificate provided has not been signed using the proper algorithm according to NIST guidelines.
- 23 The following certificates have not been signed using the proper algorithm according to NIST guidelines: RSA, ECDSA.
- 24 Some of the certificates provided have not been signed using the proper algorithm according to NIST guidelines.
- 25 All the certificates provided have been signed using the proper algorithm.
- 26 The RSA certificate provided has been signed using a weak algorithm.

27 The ECDSA certificate provided has been signed using a weak algorithm.

28 The following certificates have been signed using a weak algorithm: RSA, ECDSA.

29 Some of the certificates provided have been signed using a weak algorithm.

30 All the certificates provided have been signed using a strong algorithm.

The RSA certificate provided has been validated for more than 3 years. This  
31 means that the private key of the server will remain the same for more than 3 years. NIST guidelines suggest limiting certificate validity to 3 years maximum.

The ECDSA certificate provided has been validated for more than 3 years. This  
32 means that the private key of the server will remain the same for more than 3 years. NIST guidelines suggest limiting certificate validity to 3 years maximum.

The following certificates have been validated for more than 3 years: RSA,  
33 ECDSA. This means that the private keys of the server will remain the same for more than 3 years. NIST guidelines suggest limiting certificate validity to 3 years maximum.

Some of the certificates provided have been validated for more than 3 years.  
34 This means that the private keys of the server will remain the same for more than 3 years. NIST guidelines suggest limiting certificate validity to 3 years maximum.

35 All the certificates provided have been validated for less than 3 years.

36 The RSA certificate provided by the server could not be trusted.

37 The ECDSA certificate provided by the server could not be trusted.

38 The following certificates provided by the server could not be trusted: RSA, ECDSA.

39 Some of the certificates provided by the server could not be trusted.

40 All the certificates provided by the server are trusted.

41 The RSA certificate provided is NOT an Extended Validation (EV) certificate.

42 The ECDSA certificate provided is NOT an Extended Validation (EV) certificate.

43 The following certificates are NOT Extended Validation (EV) certificates: RSA, ECDSA.

44 Some of the certificates provided are NOT Extended Validation (EV) certificates.

- 45 All the certificates provided by the server are Extended Validation (EV) certificates.
- 46 The HTTP version of the website does not redirect to the HTTPS version. We advise to enable redirection.
- 47 The HTTP version of the website redirects to the HTTPS version.
- 48 The website includes HTTP content in HTTPS.
- 49 The Diffie-Hellman parameter's size is only \$value bits. A longer one must be generated to prevent Logjam vulnerability.
- 50 The server does not support P-256 or P-384 curves which are required by NIST guidelines.
- 51 The support of TLSv1.1 is required minimum according to NIST guidelines.
- 52 The server supports TLSv1.1 which is required minimum to comply with NIST guidelines.
- 53 The server supports TLSv1.3 which is the only version of TLS that currently has no known flaws or exploitable weaknesses.
- 54 The server does not support TLSv1.3 which is the only version of TLS that currently has no known flaws or exploitable weaknesses.
- 55 The server does not prefer cipher suites. We advise to enable this feature in order to enforce usage of the best cipher suites selected.
- 56 The server enforces cipher suites preference.
- 57 The server prefers cipher suite that has not been approved by PCI DSS requirements for at least one of the supported protocols.
- 58 For TLS family of protocols, the server prefers cipher suite(s) providing Perfect Forward Secrecy (PFS).
- 59 The server does not prefer cipher suites providing strong Perfect Forward Secrecy (PFS). We advise to configure your server to prefer cipher suites with ECDHE or DHE key exchange.
- 60 The server provides HTTP Strict Transport Security for more than 6 months: \$value seconds
- 61 The server provides HTTP Strict Transport Security for less than 6 months: \$value seconds



- 62 The server does not enforce HTTP Strict Transport Security. We advise to enable it to enforce the user to browse the website in HTTPS.
- 63 The server provides HTTP Public Key Pinning for more than 2 months: \$value seconds
- 64 The server provides HTTP Public Key Pinning for less than 2 months: \$value seconds
- 65 The server sends an invalid HPKP header: the certificate chain does not match the signature sent, or the syntax is invalid. We advise to review your configuration.
- 66 The server does not enforce HTTP Public Key Pinning that helps preventing man-in-the-middle attacks.
- 67 The server supports TLS\_FALLBACK\_SCSV extension for protocol downgrade attack prevention.
- 68 TLS\_FALLBACK\_SCSV extension prevents protocol downgrade attacks. We advise to update your TLS engine to support it.
- 69 The server is vulnerable to POODLE over TLS.
- 70 The server's response to invalid TLS packet is not compliant with RFC 4346 (section 6.2.3.2) and may be an indicator that the server is vulnerable to POODLE over TLS.
- 71 The server is not vulnerable to POODLE over TLS.
- 72 The server is vulnerable to OpenSSL padding-oracle flaw (CVE-2016-2107).
- 73 The server is not vulnerable to OpenSSL padding-oracle flaw (CVE-2016-2107).
- 74 The server may be vulnerable to OpenSSL padding-oracle flaw (CVE-2016-2107), make sure that your OpenSSL version is up to date.
- 75 The server supports a client-initiated secure renegotiation that may be unsafe and allow Denial of Service attacks.
- 76 The server does not support client-initiated secure renegotiation.
- 77 The server supports a client-initiated insecure renegotiation that is unsafe and may allow Man-In-The-Middle attacks.
- 78 The server does not support client-initiated insecure renegotiation.
- 79 The server supports OCSP stapling, which allows better verification of the

certificate validation status.

80 The server does not support OCSP stapling. Its support allows better verification of the certificate validation status.

81 The server supports secure server-initiated renegotiation.

82 The server does not support secure server-initiated renegotiation.

83 The server does not provide information if the client should accept secure server-initiated renegotiation requests.

84 TLS compression is supported by the server which may allow CRIME attack. We advise to disable this feature.

85 TLS compression is not supported by the server.

86 The server supports elliptic curves but not the EC\_POINT\_FORMAT TLS extension.

87 The server supports the EC\_POINT\_FORMAT TLS extension.

15 The server does not send EC\_POINT\_FORMAT TLS extension according to RFC 9 4492 (section 5.2, page 15).

The server version of OpenSSL is vulnerable to Heartbleed attack allowing  
88 remote compromise of your server. Update your OpenSSL to the latest version urgently!

89 The server version of OpenSSL is not vulnerable to Heartbleed attack.

90 The server is vulnerable to CVE-2014-0224 (OpenSSL CCS flaw).

91 The server may be vulnerable to CVE-2014-0224 (OpenSSL CCS flaw), make sure that your OpenSSL version is up to date.

92 The server is not vulnerable to CVE-2014-0224 (OpenSSL CCS flaw).

93 Diffie-Hellman parameter size: \$value bits

94 The server is not vulnerable to the DROWN attack.

95 The server is vulnerable to the DROWN attack. SSLv2 must be disabled urgently!

96 The server is not vulnerable to POODLE over SSL.

97 The server is vulnerable to POODLE over SSL. SSLv3 should be disabled.

- 98 The RSA certificate provided has not been signed using the proper algorithm according to HIPAA guidance.
- 99 The ECDSA certificate provided has not been signed using the proper algorithm according to HIPAA guidance.
- 10 The following certificates have not been signed using the proper algorithm according to HIPAA guidance: RSA, ECDSA.
- 10 Some of the certificates provided have not been signed using the proper algorithm according to HIPAA guidance.
- 10 The server does not support P-256 or P-384 curves which are required by HIPAA guidance.
- 10 The support of TLSv1.1 is required minimum according to HIPAA guidance.
- 10 The server supports TLSv1.1 which is required minimum to comply with HIPAA guidance.
- 10 Intermediate certificate is provided by the server.
- 10 Intermediate certificate is not provided by the server.
- 10 Server sends an unnecessary root certificate.
- 10 No unnecessary root certificate sent by the server.
- 10 The chain provided is in correct order.
- 11 Server provides certificate chain in a wrong order.
- 11 Server sends useless certificates.
- 11 Server does not send useless certificates.
- 11 The server does not support OCSP stapling for its RSA certificate. Its support allows better verification of the certificate validation status.

11 The server does not support OCSP stapling for its ECDSA certificate. Its support  
4 allows better verification of the certificate validation status.

11 The server does not support OCSP stapling for its RSA and ECDSA certificates.  
5 Its support allows better verification of the certificate validation status.

11 The server does not support OCSP for some of the provided certificates. Its  
6 support allows better verification of the certificate validation status.

11 The server supports OCSP stapling, which allows better verification of the  
7 certificate validation status.

11 HTTPS version of the website redirects to HTTP. This is a bad practice since  
8 visitors are being redirected from a secure version of the site to an insecure  
one.

11 This domain has a Certification Authority Authorization (CAA) record.  
9

12 This domain does not have a Certification Authority Authorization (CAA) record.  
0

12 The server is vulnerable to ROBOT (Return Of Bleichenbacher's Oracle Threat)  
1 vulnerability.

12 The server is not vulnerable to ROBOT (Return Of Bleichenbacher's Oracle  
2 Threat) vulnerability.

12 SPF syntax is not valid.  
3

12 There is no 'exp' or 'redirect' domain defined.  
4

12 There is no 'all' or 'a' or 'mx' or 'ptr' or 'ip4' or 'ip6' or 'exist' inside syntax.  
5

12 There is no valid domain name.  
6

12 Multiple 'redirect' modifiers detected, not in line with RFC 7208.  
7

12 Multiple 'exp' modifiers detected, not in line with RFC 7208.  
8

12 Invalid or not set DMARC version.  
9

- 13  
0 Missing 'p' (Requested handling policy) action.
- 13 Invalid 'p' (Requested handling policy) action, valid are 'none', 'reject',  
1 'quarantine'.
- 13  
2 DMARC syntax is not valid.
- 13  
3 Invalid 'rf' (Failure reporting format(s)) field value, allowed are 'iodf' or 'afrr'.
- 13 Invalid 'pct' (Sampling rate) field value, allowed is integer in range of 0 up to  
4 100.
- 13 Invalid 'ri' (Aggregate Reporting interval) field value, allowed is integer in range  
5 of 0 up to 4294967295.
- 13 Invalid 'ruf' (Reporting URI(s) for failure data) field value, valid is  
6 mailto:email@domain.com and/or http://domain.com.
- 13 Invalid 'rua' (Reporting URI(s) for aggregate data) field value, valid is  
7 mailto:email@domain.com and/or http://domain.com.
- 13 Invalid 'fo' (Failure reporting options) field value, valid are 0/1/d/s or [0/1/d/s]:  
8 [0/1/d/s].
- 13  
9 Invalid 'aspf' (SPF alignment mode) field value, valid are 'r' or 's'
- 14  
0 Invalid 'adkim' (DKIM alignment mode) field value, valid are 'r' or 's'
- 14 Invalid 'sp' (Requested handling policy for subdomains) field value, valid are  
1 'none', 'reject', 'quarantine'.
- 14  
2 DKIM syntax is not valid.
- 14  
3 Invalid DKIM version, the only valid value is 'DKIM1'.
- 14  
4 Invalid 'k' (Key type), the only valid value is 'rsa'.
- 14 Invalid 'g' (Granularity of the key), if set it must not be empty or have multiple  
5 \*.

14 Invalid 'h' (Acceptable hash algorithm(s)), valid values are 'sha1' or 'sha256' or  
6 " (empty) allowing all.

14 Invalid 's' (Service type), valid values are 'email' or '\*' or " (empty) allowing all.  
7

14 Invalid 't' (Flags type), valid values are 'y' or 's' or " (empty) no flag set.  
8

14 Test mode is on. The 'y' flag tells recipients to ignore your DKIM signature.  
9

15 Syntax error, key #key\_name# is not good DKIM key record.  
0

15 Syntax error, key #key\_name# is not good DMARC key record.  
1

15 Missing mandatory field, 'p' (Public Key).  
2

15 Public key is not valid.  
3

15 Public key is properly set, with size of #pub\_key\_size# bits.  
4

15 Public key is smaller than minimum 1024 bits.  
5

15 Public key is  $\geq$  4096 bits, it may not fit in DNS UDP query.  
6

15 Expect-CT header is properly set.  
7

15 Expect-CT header is not properly set.  
8

16 The server supports TLSv1.2.  
0

16 The server does not support TLSv1.2.  
1

16 Server's TLSv1.3 Early Data (RFC 8446, page 17) is properly implemented.  
2

16  
3 Server's TLSv1.3 Early Data (RFC 8446, page 17) is not enabled.

## Appendix 3: List of Descriptions values

### ID Value

- 1 For compatibility reasons, NIST requires the server to provide X509 certificates in version 3.
- 2 The trust model of PKI certificates currently resides on the fact they are signed by known Certificate Authority (CA), or a CA that we choose to trust. Self-signed certificates cannot be trusted.  
  
PKI certificate contains the server's public key, enabling users to encrypt messages sent to server that on its side will decrypt them using its private key.
- 3 In case of the loss or compromise of the server's private key, the certificate cannot be trusted anymore and must be revoked and marked as untrusted. However, if a certificate does not contain revocation information, it is impossible to check if it has been revoked or not.  
  
Asymmetric cryptography uses a public key to encrypt messages, or verify, signatures and a private key to decrypt or sign messages. If the key size is too short there is a risk that an attacker can forge the private key and potentially decrypt all traffic between the client and the server.
- 4 To be trusted, a certificate is hashed using a specific algorithm in order to get a statistically unique fingerprint to sign it. However, the fingerprint is not mathematically unique and an attacker may forge false certificate with the same hash value to impersonate the server if the hash algorithm used to sign it is too weak.
- 5 NIST guidelines specify that certificate should not be signed for more than 3 years. In general it is a good practice to renew private key of the server every 1 to 3 years, in order to prevent attacker forging it from the public key.
- 6 In order to be trusted, a certificate must be signed by a trusted Certificate Authority (CA), the DNS name of the server must match either the Common Name of the certificate or its Subject Alternative Names, it must be valid at the
- 7

current date (not expired) and it must not have been revoked.

8 Redirecting the users from the HTTP to the HTTPS version is a good practice to enforce secure browsing.

9 When the HTTPS version of a website contains insecure elements, it cannot be totally trusted. Attackers can still intercept these elements which can contain personal data, or tamper with them to include malicious content in.

10 It is a common best practice to configure TLS servers to have a cipher suite preference, in order to enforce the best compromise between security and performance.

1 Enforcing server preference needs to carefully order supported cipher suites.  
1 Preferring a weak cipher suite will cause every browser supporting it to use it instead of a secure one.

1 Perfect-Forward-Secrecy (PFS), based on Diffie-Hellman Ephemeral key exchange, improves global security of TLS. With RSA, an attacker can intercept encrypted communications and record them in order to decrypt them later if he manages to obtain one private key. However, with PFS, it is not possible to use the private key to decrypt messages intercepted in the past.

1 HTTP-Strict-Transport-Security directs a server to force a user's browser to make all subsequent requests via HTTPS for a specified duration.

1 Public-Key-Pinning allows a server to direct a user's browser to remember a list of trusted certificate signatures for a specified duration. These can either be server or CA certificates.

1 When using CBC cipher suites, TLS imposes padding to be filled with its own length. SSLv3 allows padding of any size, which could allow a POODLE attack.  
5 POODLE over TLS is a vulnerability that appears when a server does not check the padding value when using CBC cipher suites.

1 OpenSSL padding-oracle flaw (CVE-2016-2107, CVSSv3 5.9/10) has been introduced because of an incorrect fix for the Lucky13 vulnerability and allows attacker to reveal encrypted data. It only affects servers supporting hardware acceleration for AES encryption.

1 Client-initiated secure renegotiation (CVE-2011-1473, CVSSv2: 5.0/10) is a vulnerability that may allow Denial of Service (DoS) attacks on servers supporting it.

1 Client-initiated insecure renegotiation (CVE-2009-3555, CVSSv2: 5.8/10) is a vulnerability that may allow an attacker to successfully perform Man-in-The-



Middle attacks.

1 Heartbleed (CVE-2014-0160, CVSSv2: 5.0/10) is an OpenSSL vulnerability  
9 allowing attackers to access random portions of data stored in the server's  
9 memory. It could include user or admin passwords, private keys and other  
sensitive data.

2 OpenSSL Change-Cipher-Specs flaw (CVE-2014-0224, CVSSv2: 5.8/10) is a  
0 vulnerability affecting OpenSSL and allowing an attacker to perform Man-in-The-  
Middle attacks to downgrade the cipher suite in use between client and server.

2 DROWN vulnerability (CVE-2016-0800, CVSSv3 5.9/10) allows attackers to send  
1 specially crafted SSLv2 transactions to decrypt TLS connections on servers that  
1 use the same RSA private key.

2 POODLE vulnerability (CVE-2014-3566, CVSSv2 4.3/10) is a flaw present in the  
2 definition of the SSLv3 protocol. It may allow attackers to decrypt traffic between  
2 a browser and a server that use SSLv3 with cipher suites using CBC operation  
mode.

2 For compatibility reasons, HIPAA guidance requires the server to provide X509  
3 certificates in version 3.

2 Redirecting the users from HTTPS to HTTP is a major security risk.  
4

2 The CAA record specifies which certificate authorities are allowed to issue  
5 certificates for the domain in question.

2 ROBOT permits to decrypt intercepted TLS traffic, if the session key is encrypted  
6 with RSA algorithm and padding system is PKCS #1 1.5, by a new exploitation  
6 technique of a vulnerability discovered in 1998 by Daniel Bleichenbacher.

2 SPF is a simple email-validation system designed to detect email spoofing by  
2 providing a mechanism to allow receiving mail exchangers to check that  
7 incoming mail from a domain comes from a host authorized by that domain's  
administrators.

2 DMARC is an email-validation system designed to detect and prevent email  
8 spoofing.

2 DomainKeys Identified Mail (DKIM) provides email authentication and helps  
9 prevent potentially malicious emails from reaching recipients by using a digital  
9 signature in the email header. This validates that the email originated from the  
correct location and was not tampered with in transit. This also protects the  
reputation of the supposed sender of the email.

- 3 Expect-CT allows a site to determine if they are ready for the upcoming Chrome 0 requirements and/or enforce their CT policy.
- 3 Proper implementation of the Early Data allows a client to use zero round trip (0-1 RTT) and mitigates some vectors of the Replay Attack.

## Appendix 4: List of Highlights values

### **ID Value**

- 3 The server's certificate is untrusted.
- 4 The server's Diffie-Hellman parameter is too small, it's size is only is %d bits.
- 6 The TLS engine does not support a TLS version newer than TLSv1.0 and is outdated.
- 7 The server supports encryption protocols that are insecure and have known security flaws or weaknesses.
- 8 The server supports cipher suites that are not approved by PCI DSS requirements, HIPAA guidance and NIST guidelines.
- 9 The server supports cipher suites that are not approved by HIPAA guidance and NIST guidelines.
- 10 The server prefers cipher suites supporting Perfect-Forward-Secrecy.
- 13 The server sends an invalid HPKP header.
- 15 The server is vulnerable to POODLE over TLS.
- 16 The server is vulnerable to OpenSSL padding-oracle flaw (CVE-2016-2107).
- 18 The server is vulnerable to Heartbleed.

- 1  
9 The server is vulnerable to CVE-2014-0224 (OpenSSL CCS flaw).
- 2  
0 The server seems to require certificate-based authentication.
- 2  
1 The server configuration seems to be good, but is not compliant with PCI DSS requirements, HIPAA guidance and NIST guidelines.
- 2  
2 The server configuration seems to be good, but is not compliant with HIPAA guidance and NIST guidelines.
- 2  
3 The server configuration seems to be good, but is not compliant with PCI DSS requirements.
- 2  
4 The server is vulnerable to the DROWN attack.
- 2  
5 The server is vulnerable to POODLE over SSL.
- 2  
6 Server supports HTTPS but it is configured to redirect to HTTP. This is a major security and privacy risk.
- 2  
7 The HTTPS port (%d) is closed, data exchange with the remote web server can be intercepted.
- 2  
8 The server does not tolerate certain TLS versions. This may be a sign of improper TLS implementation.
- 2  
9 The server configuration supports only TLSv1.2 protocol, precluding users with older browsers from accessing your website.
- 6  
6 The server configuration supports only TLSv1.2 and TLSv1.3 protocols, precluding users with older browsers from accessing your website.
- 6  
7 The server configuration supports only TLSv1.3 protocol, precluding users with older browsers from accessing your website.
- 3  
0 The server configuration has a good protocol compatibility, allowing users with older browsers to access your website.
- 3  
1 The certificate's CA is not trusted by modern browsers.
- 3  
2 Test results are over one-week-old, click "Refresh" to update the results.
- 3 The server is vulnerable to ROBOT (Return Of Bleichenbacher's Oracle Threat)

3 vulnerability.

3 NIST [Update to Current Use and Deprecation of TDEA](#) abrogates 3DES  
4 authorized in the NIST guidelines.

3  
5 SPF record is missing.

3  
6 SPF record is set.

3  
7 Multiple SPF records found.

4  
3 SPF record is set properly.

3  
8 DMARC record is missing.

3  
9 DMARC record is set.

4  
4 Multiple DMARC records are found.

4  
5 DMARC record is set properly.

5  
0 DKIM record is missing.

5  
1 DKIM record is set.

5  
2 Multiple DKIM records are set.

5  
3 DKIM record is set properly.

6  
8 DKIM records are set properly.

5  
4 Email server's [SPF, DMARC and DKIM](#) are properly set.

5 Email server's [DMARC and DKIM](#) are properly set.  
5

5 Email server's [SPF and DKIM](#) are properly set.  
6

5 Email server's [SPF and DMARC](#) are properly set.  
7

5 Email server's [DKIM](#) is properly set.  
8

5 Email server's [DMARC](#) is properly set.  
9

6 Email server's [SPF](#) is properly set.  
0

6 CA of your SSL certificate is [distrusted by Google Chrome and Mozilla](#)  
2 [Firefox](#).

6 Your SSL certificate is [distrusted by Google Chrome and Mozilla Firefox](#).  
4

6 The server supports the most recent and secure TLS protocol version of TLS 1.3.  
5

7 The server has TLS 1.0 enabled. Since the 30th of June 2018 it is non-compliant  
0 with PCI DSS 3.2.1.

7 It seems that your system is blocking one of our IPs 192.175.111.228,  
1 192.175.111.229, 64.15.129.102, 64.15.129.106, 70.38.27.248, 72.55.136.156,  
1 72.55.136.199 please whitelist them for successful continuation of the test.

7 The tested service seems to be a %s.  
2

7 The server's private RSA key is weak.  
3

7 The server's private ECDSA key is weak.  
4

7 The server's private RSA and ECDSA keys are weak.  
5

7 The server's private key is weak.  
6

- 7  
7 The server's RSA certificate was signed using a weak algorithm.
- 7  
8 The server's ECDSA certificate was signed using a weak algorithm.
- 7  
9 The server's RSA and ECDSA certificate were signed using a weak algorithm.
- 8  
0 The server's certificate is signed using a weak algorithm.
- 8  
1 The remote server port %d is closed. No SSL/TSL security can be tested.
- 8  
2 The website is accessible only over unencrypted HTTP protocol.

## Appendix 5: List of Titles values

### **ID Value**

- 1 X509 CERTIFICATES ARE NOT IN VERSION 3
- 2 X509 CERTIFICATES ARE IN VERSION 3
- 3 CERTIFICATES ARE SELF-SIGNED
- 4 CERTIFICATES DO NOT PROVIDE REVOCATION INFORMATION
- 5 CERTIFICATES' KEY ARE WEAK
- 6 SERVER CERTIFICATES ARE SIGNED WITH A WRONG ALGORITHM
- 7 CERTIFICATES HAVE A WEAK SIGNATURE
- 8 CERTIFICATES HAVE BEEN SIGNED FOR MORE THAN 3 YEARS
- 9 CERTIFICATES ARE UNTRUSTED
- 1  
0 CERTIFICATES ARE TRUSTED
- 1  
1 CERTIFICATES DO NOT PROVIDE EV
- 1  
2 CERTIFICATES PROVIDE EV
- 1  
3 HTTP SITE DOES NOT REDIRECT
- 1  
4 ALWAYS-ON SSL
- 1 MIXED CONTENT

5  
1  
6 DIFFIE-HELLMAN PARAMETER WEAK  
1  
7 DIFFIE-HELLMAN PARAMETER SIZE  
1  
8 NO SUPPORT FOR COMMON CURVES  
1  
9 NO SUPPORT OF TLSv1.1  
2  
0 TLSv1.1 SUPPORTED  
2  
1 TLSv1.3 SUPPORTED  
2  
2 NO SUPPORT OF TLSv1.3  
2  
3 SERVER DOES NOT HAVE CIPHER PREFERENCE  
2  
4 SERVER HAS CIPHER PREFERENCE  
2  
5 SERVER PREFERS WEAK CIPHER SUITES  
2  
6 SERVER PREFERS CIPHER SUITES PROVIDING PFS  
2  
7 SERVER DOES NOT PREFER CIPHER SUITES PROVIDING PFS  
2  
8 SERVER PROVIDES HSTS WITH LONG DURATION  
2  
9 SERVER PROVIDES HSTS WITH SHORT DURATION  
3  
0 SERVER DOES NOT PROVIDE HSTS  
3  
1 SERVER PROVIDES HPKP WITH LONG DURATION  
3  
2 SERVER PROVIDES HPKP WITH SHORT DURATION  
3  
3 SERVER PROVIDES INVALID HPKP  
3  
4 SERVER DOES NOT PROVIDE HPKP  
3  
5 TLS\_FALLBACK\_SCSV  
3  
6 POODLE OVER TLS

3  
7 CVE-2016-2107

3  
8 SERVER SUPPORTS CLIENT-INITIATED SECURE RENEGOTIATION

3  
9 SERVER DOES NOT SUPPORT CLIENT-INITIATED SECURE RENEGOTIATION

4  
0 SERVER SUPPORTS CLIENT-INITIATED INSECURE RENEGOTIATION

4  
1 SERVER DOES NOT SUPPORT CLIENT-INITIATED INSECURE RENEGOTIA-  
1 TION

4  
2 SERVER SUPPORTS OCSP STAPLING

4  
3 SERVER DOES NOT SUPPORT OCSP STAPLING

4  
4 SERVER-INITIATED SECURE RENEGOTIATION

4  
5 SERVER SUPPORTS TLS COMPRESSION

4  
6 SERVER DOES NOT SUPPORT TLS COMPRESSION

4  
7 EC\_POINT\_FORMAT EXTENSION

4  
8 HEARTBLEED

4  
9 CVE-2014-0224

5  
0 DROWN

5  
1 POODLE OVER SSL

5  
2 HTTPS SITE REDIRECTS TO HTTP

5  
3 DNSCAA

5  
4 ROBOT

5  
5 SPF

5  
6 DMARC

5  
7 DKIM

5  
8 EXPECT-CT



```

8
5
9 TLSv1.2 SUPPORTED
6
0 NO SUPPORT OF TLSv1.2
6
1 TLSv1.3 EARLY DATA
  
```

## Appendix 6: List of Error messages

| <b>error_id</b> | <b>error</b>  |
|-----------------|---|
| 1               | You have performed N tests in the last 3 minutes. The system is currently busy, please try again a bit later.   |
| 2               | You have performed N tests in the last 24 hours. The system is currently busy, please try again a bit later.  |
| 3               | Sorry, our systems are very busy now, we are working on the issue. Please try again in a few minutes.   |
| 4               | You reached the limit of N concurring running tests. Please wait until at least one of them is finished.  |
| 5               | Sorry, your API key is invalid or has expired. Please double-check it or contact us.  |
| 6               | Test is forbidden.  |
| 7               | The domain name cannot be resolved.   |
| 9               | The domain name does not exist.   |
| 10              | An error has occurred while checking DNS records of domain.   |
| 11              | Invalid IP address.   |
| 12              | Error with token. Our API has changed, please take look at documentation at <a href="https://www.immuniweb.com/ssl/#api">https://www.immuniweb.com/ssl/#api</a> |
| 13              | We could not conduct the requested test because a timeout occurred.   |

|    |  |
|----|--|
|    |  |
| 14 | Arbitrary error from the engine.   |
| 15 | Something went wrong with this test. Our engineers were notified and will start working in it shortly. Please try again later. |
| 16 | Domain name was resolved in an invalid IP address.   |
| 17 | An error occurred while encoding results.  |
| 18 | Test does not exist.   |
| 19 | Too many downloads of PDF.   |
| 20 | Not logged in.   |